



Installation instructions and information Weyer®

The installation must be carried out dust-free. The optimal temperature for installation is from 20° to max. 40° Celsius

- 1.) Clean and degrease the mounting surface thoroughly. All polishing and wax residues must be removed.
- 2.) Check the fit of the vehicle with the product (do not peel off the protective film on the adhesive strips)
- 3.) Mark the adhesive positions of the outer edges on the vehicle part
- 4.) Remove protective papers from the adhesive tape. (ATTENTION: Adhesive tape on the product adheres immediately!)
- 5.) Position the product in the marked areas without correcting it. Start from the top and then press the bumper protector onto the entire surface. Press down well – glue adheres immediately!
- 6.) Please do not wash your car for the next 24 hours!

ATTENTION ! Once glued on, it is no longer possible to correct the aperture, so it must be placed in the correct position from the beginning.

If the bumper protector is applied to an insufficiently degreased surface, the tape will not be able to adhere properly, which can cause damage to the vehicle. In this case, the manufacturer cannot be held liable for any damage caused by improper installation.

Safety recommendations:

- Do not allow to stick to the skin.
- Do not mount at very high temperatures.
- Keep away from children and animals.

GB – Instruction

Installation must be carried out in a dust-free environment at a temperature of 20° to max. 40 degrees Celsius.

Work steps:

- 1.) The mounting surface must be thoroughly cleaned and degreased. All polish and wax residues must be thoroughly removed from the adhesive surface.
- 2.+3.) Check the fit of the product on your vehicle (do not remove the protective film from the adhesive strip) and mark the adhesive positions of the outer edges on the vehicle part.
- 4.) Remove the protective paper from the adhesive tape on the loading sill protector. (CAUTION: The adhesive tape on the product sticks immediately!)
- 5.) Now position the product on the marked area without making any corrections. Start at the top and then press the loading sill protector onto the entire surface. Press down firmly – the adhesive reacts immediately!
- 6.) Please do not wash your car for the next 25 hours!

CAUTION! Once the trim has been applied, it cannot be adjusted, so it must be positioned correctly from the outset.

CAUTION!!! If the bumper protector is applied to an insufficiently degreased surface, the adhesive tape may not adhere properly, which could result in damage to the bumper. In this case, the manufacturer cannot be held liable for damage caused by improper installation.

Safety recommendations:

- Do not allow to stick to skin.
- Do not install at very high temperatures.
- Keep away from children and animals.

NL

INSTALLATION INSTRUCTIONS

Thoroughly clean and degrease the surface of the bumper.

Mark the place where the strip is to be applied. Remove the protective film from the adhesive tape.

Attach the bumper guard to the marked location and press it down evenly.

PAY ATTENTION !! If the bumper guard is applied to an insufficiently degreased surface, the tape may not adhere properly, which can lead to damage to the bumper. In this case, the manufacturer cannot be held liable for damage resulting from incorrect installation.

Precautionary Notes:

- Do not leave it on the skin.
- Do not apply at very high temperatures.
- Keep away from children and animals.

IT

INSTALLATION INSTRUCTIONS

Clean and degrease the bumper surface thoroughly.

Mark the location where the tape should be applied. Remove the protective film from the tape.

Attach the bumper guard to the marked location and press evenly.

CAREFUL!!! If the bumper guard is applied to an insufficiently degreased surface, the tape may not adhere properly, which can damage the bumper. In this case, the manufacturer cannot be held responsible for damage resulting from improper installation.

Safety Recommendations:

- Do not stick to the skin.
- Do not paint at very high temperatures.
- Keep out of reach of children and pets.

DK

INSTALLATION INSTRUCTIONS

Clean and degrease the bumper surface thoroughly.

Mark the location where the strip is to be mounted. Remove the protective foil from the adhesive tape.

Attach the bumper guard to the marked spot and press it in place evenly.

NOTE !! If the bumper guard is mounted on a surface that is not sufficiently degreased, the adhesive tape may not adhere properly, which may result in damage to the bumper. In this case, the manufacturer cannot be held responsible for damage caused by incorrect installation.

Safety recommendations:

- Do not stick to the skin.
- Do not install at very high temperatures.
- Keep away from children and animals.

IT

INSTALLATION INSTRUCTIONS

Clean and degrease the surface of the bumper thoroughly.

Mark the spot where the strip should be applied. Remove the protective film from the adhesive tape.

Attach the bumper protector to the marked spot and press down evenly.

CAUTION !! If the bumper protector is applied to a surface that is not sufficiently degreased, the adhesive tape may not adhere properly, causing damage to the bumper. In such a case, the manufacturer cannot be held liable for damage caused by incorrect installation.

Safety recommendations:

- Do not let it stick to the skin.
- Do not mount at very high temperatures.
- Keep out of reach of children and pets.

SE

INSTALLATION GUIDANCE

Clean and degrease the bumper surface thoroughly.

Mark the location where the strip should be attached. Remove the protective film from the tape.

Attach the bumper cover to the marked spot and press it in place evenly.

WARNING !! If the bumper cover is mounted on a surface that is not sufficiently degreased, the tape may not adhere properly, which can lead to damage to the bumper. In this case, the manufacturer cannot be held responsible for damage resulting from improper installation.

Safety Recommendations:

- Do not stick to the skin.
- Do not mount at very high temperatures.
- Keep away from children and animals.