



			•	
	וחו	~+	10	
Гυ	ш	L	10	113
		_	•	• • •

- Easy and labour-saving attachment to the towbar with leverless, patented IQ quick-release fastener
- Removable spacers with single-hand operation
- New extra-wide wheel rails for tyre widths up to 4.5 inches
- Foldable wheel rail and lamp unit
- Ratchet system for securely attaching the wheels to the wheel rail
- At only 18 kg, it's particularly light and, thanks to this low dead weight, allows for a large payload without additional rigging
- Convenient release of the folding function with foot lever
- Quick-release lever for fixing the wide carrier frame
- Anti-theft device with simultaneous locking
- Quality product made in Germany with 3-year warranty

Technical details				
Number of bikes	3			
Dimensions (mounted)	119 x 89 x 78 cm (WxHxD)			
Dimensions (folded)	61 x 22 x 82 cm (WxHxD)			
Weight	18 kg			
Wheel rail distance	22/20 cm			
Payload (support load ≥ 75 kg)	max. 57 kg			
Payload (support load ≥ 90 kg)	max. 72 kg			
Max. bike centre distance	130 cm			
Folding angle	60°			
Minimum requirements of the towbar				
Material quality	min. St 52-3			
Support load	min. 75 kg			
Diameter of towbar neck	min. Ø 28.5 mm			



T.



SPACER WITH

MAX. 72 KG PAYLOAD

18 KG DEAD WEIGHT







60° FOLDING

SMALL FOLDING SIZE

EXTRA EASY







WITHOUT TOOLS

ANTI-THEFT DEVICE

SUITABLE FOR E-BIKES

## Accessories:

Transport and storage bag Art. 25030



Drive-on and drive-over ramp (foldable) Art. 19950



Toothed belt conversion kit for fatbikes Art. 25010



## Multiple test winner:









With distance control

